Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

MEAN WELL

SWITCHING POWER SUPPLY

ISO-9001 CERTIFIED MANUFACTURER

PS-25

SERIES

Jameco Part Number 212361 (PS-25-3.3)

.LOW COST, HIGH RELIABILITY
.105°C OUTPUT CAPACITOR
.INTERNATIONAL AC INPUT RANGE
.HIGH EFFICIENCY, LOW WORKING TEMPERATURE
.SOFT-START CIRCUIT, LIMITING AC SURGE CURRENT
.SHORT CIRCUIT, OVERLOAD, OVER VOLTAGE PROTECTED
.COMPACT SIZE, LIGHT WEIGHT
.100% FULL LOAD BURN-IN TEST
.BUILT IN EMI FILTER, LOW RIPPLE NOISE

MODEL / SPECIFICATION	PS-25 -3.3	PS-25 -5	PS-25 -7.5	PS-25 -12	PS-25 -13.5	PS-25 -15	PS-25 -24	PS-25 -27	PS-25 -48
DC OUTPUT VOLTAGE	3.3V	5V	7.5V	12V	13.5V	15V	24V	27V	48V
OUTPUT V. TOLERANCE	±3%	±2%	±2%	±2%	±2%	±2%	±2%	±2%	±2%
OUTPUT RATED CURRENT	5A	5A	3.3A	2.1A	1.9A	1.7A	1A	0.9A	0.5A
OUTPUT CURRENT RANGE	0-5A	0-5A	0-3.3A	0-2.1A	0-1.9A	0-1.7A	0-1A	0-0.9A	0-0.5A
RIPPLE & NOISE (Vp-p)	80m	80m	80m	100m	100m	100m	240m	240m	350m
LINE REGULATION	±0.5%	±0.5%	±0.5%	±0.3%	±0.3%	±0.3%	±0.2%	±0.2%	±0.2%
LOAD REGULATION	±2.5%	±2%	±2%	±1%	±1%	±1%	±0.5%	±0.5%	±0.5%
DC OUTPUT POWER	16.5W	25W	24.8W	25.2W	25.7W	25.5W	24W	24.3W	24W
EFFICIENCY	66%	74%	76%	78%	78%	78%	79%	79%	79%
DC VOLTAGE ADJ.	---								
INPUT VOLTAGE RANGE	85~264VAC 47~63Hz; 120~370VDC								
AC CURRENT	0.65A/115V 0.4A/230V								
INRUSH CURRENT	COLD START 40A								
LEAKAGE CURRENT	<0.5mA/240VAC								
OVERLOAD PROTECTION	ABOVE 105% TYPE:PULSING HICCUP SHUTDOWN RESET:AUTO RECOVERY								
OVER VOLTAGE PROTECTION	115%~135%								
OVER TEMP. PROTECTION	U1 Tj 135°C TYPICALLY POWER SHUTDOWN								
TEMP. COEFFICIENT	±0.03% / °C (0~50°C)								
SETUP, RISE, HOLD UP TIME	200ms, 30ms, 17ms/115VAC 200ms, 20ms, 80ms / 230VAC								
VIBRATION	10~500Hz, 2G 10min./1cycle, PERIOD FOR 60min. EACH AXES								
WITHSTAND VOLTAGE	I/P-O/P:3KVAC I/P-FG:1.5KVAC O/P-FG:0.5KVAC								
ISOLATION RESISTANCE	I/P-O/P, I/P-FG:500VDC / 100M Ohms								
WORKING TEMP., HUMIDITY	-10°C~+60°C(REFER TO OUTPUT DERATING CURVE), 20%~90% RH								
STORAGE TEMP., HUMIDITY	-20°C~+85°C, 10%~95% RH								
DIMENSION	107*61*30mm								
WEIGHT	0.15Kgs								
SAFETY STANDARDS	UL1950, TUV EN60950 APPROVED								
EMC STANDARDS	CISPR22 (EN55022), IEC1000-4-2,3,4,5 IEC1000-3-2,3 VERIFICATION								

NOTE :
1.ALL PARAMETERS ARE SPECIFIED AT 230VAC INPUT, RATED LOAD, 25°C 70% RH. AMBIENT.
2.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR.
3.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.

2002-03-05

BLOCK DIAGRAM



fosc : 100KHz

OUTPUT DERATING



STATIC CHARACTERISTICS



DIMENSION:mm[inch]

- TERMINAL PIN NO. ASSIGNMENT
  - CN1 : MOLEX 41791-03
    PIN 1,3 : AC INPUT
  - CN2 : MOLEX 41791-04
    PIN 1,2 : DC OUTPUT +V
    PIN 3,4 : DC OUTPUT -V
- MATING CONNECTORS
  - CN1,2 MATING CONNECTOR TYPE MOLEX 2139 AND 3069 SERIES OR EQUIVALENT WITH MOLEX 2478 AND 2578 OR EQUIVALENT CRIMP TERMINALS.